39.5"





Electrical Service: 120V/20amp

NEMA 5-20R GFCI Outlet









- 1-2 Persons Capacity
 Premium Pacific Cedar Exterior Finish
 Insulated Sustainable Composite Cold Plunge Tub
 • Exterior Dimensions: 42" Wide x 39.5" Tall
- **Built-in Interior Seat**
- Premium Pacific Cedar Step for Easy Entry and Exit
- Blue Cover with Child Safety Latches

- 5 Year Warranty on Structure
 Dry Weight: 250 lbs
 Total Weight with Water: Approx. 1200 lbs

DCT-B-042-PLPC



1-2 Person Pacific Cedar Stainless Steel **Barrel Plunge**

Barrel Plunge



ELECTRCIAL

Electrical Service: 120V/20amp

NEMA 5-20R GFCI Outlet









- 1-2 Persons Capacity
 Premium Pacific Cedar Exterior Finish
 Insulated 304 Stainless Steel Cold Plunge
- Exterior Dimensions: 42" Wide x 39.5" Tall
- **Built-in Interior Seat**
- Premium Pacific Cedar Step for Easy Entry and Exit
- Blue Cover with Child Safety Latches

- 5 Year Warranty on Structure
 Dry Weight: 250 lbs
 Total Weight with Water: Approx. 1200 lbs

DCT-B-042-SSPC



Spa Chilling System

.6 Horsepower Smart Chilling System





Electrical Service: 120V/20amp/60Hz

NEMA 5-20R GFCI Outlet



610W / 5.1 AMPS





FEATURES

- .6 HP Powerful Cooling (Min 37°F / 3°C)
- 1-3°F of Cooling Every 40 Minutes
- Heat Function (Max 80°F / 26°C)
- Wifi Enabled Mobile App Controlled
- 5" Touchscreen Digital Display
 15-Micron Filtration (4.5" Replaceable
- Automated Ozone Sanitation
- Self-Priming High-Flow Rate Pump
- GFCI Protection
- Includes: Hose Kit, Filter Wrench, & Two Filter Cartridge Replacements
- Lockable Casters
- Steel Reinforced Inset Carrying Handles
- Quick Connect Fittings
- Overheating Protection
- Max Temperature Exposure 85°F
- Min Temperature Exposure 32°F
- 1 Year Warranty
- Weight: 50 lbs²
- Dimensions (LxWxH): 17"x11"x19"

DCT-SY-06-HC



Spa Chilling System

.8 Horsepower Smart Chilling System



ELECTRCIAL

Electrical Service: 120V/20amp/60Hz

NEMA 5-20R GFCI Outlet



725W / 6.1 AMPS





FEATURES

- .8 HP Powerful Cooling (Min 37°F / 3°C)
- 1-3°F of Cooling Every 30 Minutes
- Heat Function (Max 80°F / 26°C)
- Wifi Enabled Mobile App Controlled
- 5" Touchscreen Digital Display
 15-Micron Filtration (10.5" Replaceable
- Automated Ozone Sanitation
- Self-Priming High-Flow Rate Pump
- GFCI Protection
- Includes: Hose Kit, Filter Wrench, & Two Filter Cartridge Replacements
- Lockable Casters
- Steel Reinforced Inset Carrying Handles
- Quick Connect Fittings
- Overheating Protection
- Max Temperature Exposure 90°F
- Min Temperature Exposure 32°F
- 1 Year Warranty
- Weight: 50 lbs²
- Dimensions (LxWxH): 19"x14"x21"

DCT-SY-08-HC



Spa Chilling System

1 Horsepower Smart Chilling System





Electrical Service: 120V/20amp/60Hz

NEMA 5-20R GFCI Outlet



1170W / 9.75 AMPS





FEATURES

- 1 HP Powerful Cooling (Min 37°F / 3°C)
- 1-3°F of Cooling Every 20 Minutes
- Heat Function (Max 80°F / 26°C)
- Wifi Enabled Mobile App Controlled
- 5" Touchscreen Digital Display
 15-Micron Filtration (10.5" Replaceable
- Automated Ozone Sanitation
- Self-Priming High-Flow Rate Pump
- GFCI Protection
- Includes: Hose Kit, Filter Wrench, & Two Filter Cartridge Replacements
- Lockable Casters
- Steel Reinforced Inset Carrying Handles
- Quick Connect Fittings
- Overheating Protection
- Max Temperature Exposure 95°F
- Min Temperature Exposure 32°F
- 1 Year Warranty
- Weight: 50 lbs²
- Dimensions (LxWxH): 22"x16"x22"

DCT-SY-10-HC

